

# AB PROFIT HOGA AUR BHI ZYAADA



**FE**  
Series

**BS6 P2**  
Phase 2 Ready

- ✓ Safer
- 💡 Smarter
- ♻️ Greener
- ⚙️ Better Fuel Efficiency
- 💰 Lower Total Cost of Ownership

**TATA**  
**ULTRA**  
T.9

**TATA TRUCKS**  
**DESH KE TRUCKS**

## Technical Specifications

Models	Ultra T.9 DCR 125B6PH2M5		
Engine	4SPCR BSVI Ph2		
Engine Type	4 Cylinder in line water cooled direct Injection diesel engine with intercooler		
Engine Displacement	2 956 cc		
Power	74.5 kW (100 Ps) Light Mode   92 kW Heavy Mode (125 Ps) @ 2 800 r/min		
Torque	360 Nm @ 1 400 - 1 800 r/min (Light Mode)   300 Nm @ 1 000 - 2 200 r/min (Heavy Mode)		
Clutch	Single plate dry friction type - 280 mm dia (with Booster)		
Gearbox	G400, 5 Speed, Manual Synchromesh Gearbox (5F, 1R)		
Gearbox Ratio	1st - 6.45, 2nd - 3.66, 3rd - 2.29, 4th - 1.49, 5th - 1.00, Rev - 6.26		
Suspension - Front Type	Parabolic leaf spring with Hydraulic Double acting Telescopic Shock Absorbers		
Suspension - Rear Type	Semi elliptical leaf spring,		
Tyres	7.50R16 - 16PR Low CRR Tyre (Front-2 / Rear - 4)		
Cabin Type	Ultra Narrow Day Cabin - 1 905 mm		
Steering Type*	Tilt & Telescopic Power Steering (4Spoke)		
Brakes Type	Dual Circuit Full Air S* Cam Brakes With Auto Slack Adjuster (Drum - Drum) - 325 mm		
Ground Clearance	183 mm		
Gradeability	20.20 %		
Rear Axle	Banjo Type - Single reduction hypoid gears, fully floating axle shafts - RAR: 4.857		
Battery	12V, 100 Ah		
Fuel Tank Capacity	90 l HD Polymer Fuel Tank		
Load Body Variants	CAB & HSD		
GVW	9 150 kg		
FAW	3 330 kg		
RAW	5 820 kg		
Long member Size (L x B x H)	200 mm x 60 mm x 5 mm		
Wheelbase	3 550 mm	3 920 mm	4 530 mm
TCD	13 900 mm	15 200 mm	18 000 mm
Variants	CAB HSD	CAB HSD	CAB HSD
Load Body Dimensions (L x W x H)	NA 4 350 mm x 1 962 mm x 1 835 mm	NA 5 218 mm x 1 962 mm x 1 835 mm	NA 6 127 mm x 1 962 mm x 1 835 mm
Warranty	3 year or 3 00 000 km		
Seating Capacity	D + 2		
DEF Tank Size	18 l		
FIP Model	Delphi CR System (1 800 + bar pressure)		
Service Interval	1 Year or 40 000 km, Hub Greasing 120 000 km, Gear Oil Change Interval - 2 40 000 km		

## Key Features & Benefits



THU Bearing



1905 mm Narrow Cabin



Gear Shift Advisor



Low CRR Tyre



Fleetedge Telematics



Dual Mode FE Switch  
Light & Heavy

## Applications



Cement, Building  
Construction



Parcel & Courier  
E Commerce



Pharma



Fruits &  
Vegetables



FMCG



LPG Cylinder



Food grains



Industrial Goods



Containers  
& Reefers



White Goods



**TATA MOTORS**

To know more, visit your nearest Tata Motors dealership

[www.light-trucks.tatamotors.com](http://www.light-trucks.tatamotors.com)

📞 18 00 20 97 979 Follow us on